

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/084743 A1

(51) International Patent Classification⁷: **A61B 17/70**

(21) International Application Number:
PCT/IT2004/000148

(22) International Filing Date: 24 March 2004 (24.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
FI2003 A 000084 28 March 2003 (28.03.2003) IT

(71) Applicants (for all designated States except US): **SMART HOSPITAL S.R.L.** [IT/IT]; Via Provinciale, 36, I-55060 San Martino in Freddana (IT). **COUSIN BIOTECH S.A.S.** [FR/FR]; Rue Abbe Bonpain, F-59017 Wervicq-Sud (FR).

(71) Applicant and

(72) Inventor: **PETRINI, Piero** [IT/IT]; Via dell'Acacia, 141, I-06100 Perugia (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **DENEUVILLIERS, Guy** [FR/FR]; 42, Allez des Chardonnerets, F-62155 Marlimont (FR).

(74) Agents: **MANNUCCI, Michele** et al.; Uff. Tecn. Ing. A. Mannucci S.r.l., Via della Scala, 4, I-50123 Firenze (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **INTERLAMINAR VERTEBRAL PROSTHESIS**



(57) Abstract: The prosthesis comprises an elastic body (1) inserted between two adjacent vertebrae (L2, L3) against the laminar arch (A2, A3) of each vertebra and means (3, 5) for securing the elastic body to said laminar arches.

WO 2004/084743 A1

“INTERLAMINAR VERTEBRAL PROSTHESIS”

DESCRIPTION

Technical field

This invention relates to an intervertebral prosthesis capable of redistributing between two adjacent vertebrae the imposed load created by degeneration of the disk located between these vertebrae without immobilizing them, but allowing them the possibility of following normal movements of the spine.

Background of the invention

Prostheses comprising a part made of deformable material are known. French Patent 2,623,085 in the name of Francis Henri Breard describes a deformable block having two opposite V-shaped ends which can be inserted between the spinous processes of two adjacent vertebrae. The block is secured there through ligatures passing through lateral inclined holes. A prosthesis according to a similar concept is described in European patent publication 0,322,334 A1, inventor Jean-Jacques Bronsard, in which one or more hollow cylindrical elastic cushions are located between the spinous processes of two adjacent vertebrae and secured there through a ligature passing through them. Other interspinous prostheses of various shapes are described in documents FR 2,717,675 and FR 2,775,183, both in the name of Jean Taylor.

All the abovementioned prostheses are located between the spinous processes and are secured there in order to at least partly absorb the load transmitted between these vertebrae. However, the centre of gravity of the spine is located behind the vertebral body, as a result of which these prostheses – being located between the spinous processes – are somewhat off centre in relation to the centre of gravity. This has the consequence that only a smaller part of that load is in fact taken up by the prosthesis. Furthermore, since for the same reason bending movements of the spine tend to cause the spinous processes to move apart or come together by a relatively large amount, these prostheses can have a tendency to tilt, with the lower part slipping backwards, and therefore losing

12 APR 2006

effectiveness.

Objects and summary of the invention

The object of the invention is to provide an intervertebral prosthesis which reduces or overcomes at least some of the disadvantages and drawbacks of the known intervertebral prostheses discussed above.

According to the invention, an intervertebral prosthesis is provided, which includes an elastic body suitable for insertion between two adjacent vertebrae alongside the laminar arch of each vertebra, and means for securing the elastic body to said laminar arches.

In this way the distance between the axis of said elastic body and the centre of gravity of the vertebral bodies is substantially reduced in comparison with the known situations described above. The advantages of locating a damping system which acts interlaminarly are undoubted, as it is unanimously recognized that in degenerative disease of the disk the fulcrum of the functional unit is gradually displaced towards the rear and specifically falls in the interlaminar zone behind the joint surfaces of the vertebrae.

In a preferred embodiment said securing means comprise a plate at each end of the elastic body for anchoring to the laminar arch. Said plates are preferably substantially rigid, preferably more rigid than said elastic body. Each plate has means for connection to the respective vertebra.

In a particularly advantageous embodiment of the invention, said means may include, for each plate, three projections which when the plate is fitted in position face towards the corresponding laminar arch, and in particular: a median projection of a thin shape which can be inserted into the spinal foramen of the vertebra without compressing the spinal cord, and two projections spaced apart laterally for insertion into contact with the posterior surfaces of the laminae forming the laminar arch. The assembly of the plates and the elastic body is held together through at least one ligature passing through holes made in the plates and in the elastic body, holes which, when the assembly is fitted, are in line with each other.

A prosthesis of this kind is especially suitable for the lumbar vertebrae,

from L1 to L5, and also between L5 and S1. Because the laminar arch of the vertebrae has a flattened transverse section which is inclined with respect to the axis of the spine, the shapes of the plates generally differ from each other, and can vary according to the pair of vertebrae between L1 and S1 involved.

The elastic body inserted between the plates is of a material which is flexible in all directions, so as to adjust to complex relative movements of the vertebrae. The ligature used to connect the end plates with the elastic body also preferably has some elasticity, and can be provided already attached to a right bevelled needle which is caused to pass through the holes in the plates and the elastic body and secured by rivets once tensioned. The surplus ligature is then cut off and removed.

Preferably, each of said anchoring plates has a groove on the surface in contact with the elastic body into which a tip of divaricator forceps can be inserted in order to move them apart. The technique of fitting the prosthesis according to the invention provides for positioning each plate on the laminar arch of the corresponding vertebra. Then fitting the tips of the divaricator forceps into the grooves in the plates, while these are held in position through the tips of the forceps, the vertebrae are drawn apart placing tension on the ligatures, making it possible for the elastic body to be inserted between the plates, especially from the side, and for the assembly to be subsequently ligated. The technique in fact provides for mono- and/or bilateral access to the intervertebral space and safeguards the supraspinous ligament, with minimum detachment of the ligamentum flavum in the so-called "safety zone" for insertion of the end plates.

Further advantageous embodiments and possible additional features of the prosthesis according to the invention are set forth in the attached claims.

Brief description of the drawings

The invention will be better understood from the following description and appended drawing which illustrates a non-restrictive embodiment of the invention. In the drawing:

Figures 1 and 2 show views of the assembled prosthesis in elevation, from the side and rear respectively,

Figure 3 shows a side view of the prosthesis fitted in position and in cross-section along the sagittal plane,

Figure 4 shows a rear view along IV-IV in Figure 3,

Figures 5 and 6 show cross-sectional views in plan along V-V and from beneath along VI-VI in Figure 3 respectively,

Figure 7 shows a perspective view of a component of the prosthesis in Figure 1;

Figure 8 shows a perspective view of the prosthesis during a stage of application using divaricator forceps;

Figure 9 shows a lateral view of a further embodiment of the prosthesis according to the invention;

Figures 10 and 11 show end views according to line X-X and XI-XI of Fig.9; and

Figure 12 shows a lateral view of the prosthesis of Figures 9-11 fitted on the spine

Detailed description of preferred embodiments

With reference to Figures 1, 2 and 3, a prosthesis according to the invention which has to be inserted between a pair of lumbar vertebrae, for example L2, L3, comprises an elastic body 1 of broadly cylindrical shape located between two end plates 3, 5 each of which can be anchored to the laminar arch of a corresponding vertebra and each of which has a straight groove 3S, 5S on the surface in contact with body 1 orientated at right angles to the sagittal plane along the line X-X (Figure 2). Once fitted the various parts of the prosthesis are stably secured together through two lengths of ligament 7, 9 each of which is caused to pass through corresponding holes 3D, 5D; 3E, 5E; 1D, 1E in plates 3, 5 and elastic body 1 respectively, by means of a straight needle which is not shown, and is secured after being tensioned through rivets 11 fitted to the outer surfaces of plates 3, 5.

Body 1 is made of elastic material which is flexible in all directions and

may be coated with flexible material (e.g. polyester, etc.) suitable for remaining in contact with human tissues without damaging them or giving rise to rejection reactions.

With reference to Figures 1, 2, 3, 4 and 5, upper plate 3 has on its upper surface a central tooth 3A located on the side of the perimeter of the plate facing the spinal foramen CM and a pair of lateral teeth 3B, 3C located symmetrically on opposite sides of the sagittal plane along line X-X, these teeth facing upwards and being slightly inclined with their upper ends towards the left (looking at Figure 3). Having this shape, this plate is dimensioned so that it can be inserted from beneath against the laminar arch A2 (Figure 5) of upper vertebra L2 with central tooth 3A located between the inner central part of laminar arch A2 and spinal foramen CM, and lateral teeth 3B, 3C each in contact with a lateral outer surface (FB, FC) of the corresponding lamina forming said laminar arch A2.

With reference to Figures 1, 2, 3, 4 and 6, lower plate 5 has on its lower surface a central tooth 5A located on the side of the perimeter of the plate facing the spinal foramen CM and a pair of lateral teeth 5B, 5C located symmetrically on opposite sides of the sagittal plane along the line X-X (Figure 5), these teeth facing downwards and being slightly inclined with their lower ends towards the right (looking at Figure 3). Having this shape plate 5 is dimensioned in such a way that it can be inserted downwards against the laminar arch A3 (Figure 6) of lower vertebra L3, with central tooth 5A located between the inner central part of laminar arch A3 and the spinal foramen CM, and lateral teeth 5B, 5C each in contact with a lateral outer surface GB, GC of the corresponding lamina forming said laminar arch A3.

Once plates 3, 5 have been fitted to corresponding vertebrae L2, L3, the terminal tips P3, P5 (Figure 8) of divaricator forceps P are inserted into grooves 3S, 5S and plates 3, 5 together with vertebrae L2, L3 to which they are fitted are moved apart as far as possible. During this stage the divaricator forceps also have the function of holding the plates in position. Thus elastic body 1 can be inserted laterally between plates 3, 5 without

having to interrupt the supraspinal ligament, and then ligaments 7, 9 can be passed through appropriate holes 3D, 3E; 5D, 5E in plates 3, 5 and 1D, 1E of body 1 and fixed thereto through rivets 11.

Because the dimensions of the vertebrae vary from one individual to another, and for one individual from one vertebra to another along the length of the spine, these plates are manufactured in various sizes so as to cover a wide range of possibilities of use.

Figures 9-12 show a second embodiment of prosthesis according to the invention. The same reference numbers are used to designate the same or equivalent parts or elements of the prosthesis.

The elastic body 1 has a slightly different shape and is not cylindrical but rather has planar lateral surfaces. Such shape can be used also in the embodiment of the previous figures. The projections 3A, 3B, 3C and 5A, 5B and 5C are shown in a different shape and dimension by way of example. The shape of these portions of the prosthesis can depend upon the location where it has to be applied and/or the morphological characteristics of the patient which has to receive the prosthesis.

The main difference of the prosthesis of Figures 9-12 with respect to the previously described embodiment consists in the presence of an auxiliary ligament 21 which is used to connect the two spinous processes SP1 and SP2 of the adjacent vertebrae designated L in Figure 12, between which the prosthesis is inserted. The ligament 21 embraces the two spinous processes SP1, SP2 and provides an augmentation to the supraspinal ligament and a replacement for the interspinous ligament, said auxiliary ligament 21 extending along the same inclined development of the interspinous ligament, i.e. from the apex of the upper spinous process to the base of the lower spinous process.

The ligament 21 is anchored to the two plates 3, 5 by means of suitable connection or anchoring devices. In the example shown in Figures 9-12, each plate 3, 5 is provided with a pair of opposite hooks designated 3H and 5H respectively, on both sides of the plates. The hooks 3H and 5H are oppositely oriented: the hooks 3H are opened backwards, i.e. opposite the

spinal foramen, while the hooks 5H are opened towards said spinal foramen.

It will be understood that the drawing only shows an example provided as a practical embodiment of the invention, and the invention may vary in shape and arrangement without thereby going beyond the scope of the concept underlying the invention itself. Any reference numbers included in the appended claims are purely to assist a reading of the claims with reference to the description, and do not restrict the scope of the protection represented by the claims.

CLAIMS

1. Intervertebral prosthesis characterized in that it comprises an elastic body (1) designed to be inserted between two adjacent vertebrae (L2, L3) against the laminar arch (A2, A3) of each vertebra, and means (3, 5) for securing the elastic body to said laminar arches.

2. Prosthesis according to Claim 1, characterized in that said securing means comprise an anchoring plate (3, 5) for each end of the elastic body for anchoring to the corresponding laminar arch (A2, A3) of each of said vertebrae.

3. Prosthesis according to claim 2, characterized in that said plate is substantially rigid.

4. Prosthesis according to claim 2 or 3, characterized in that each plate has a plurality of projections (3A, 3B, 3C; 5A, 5B, 5C) shaped and arranged for co-acting with the corresponding laminar arch of each vertebra.

5. Prosthesis according to claim 4, characterized in that each plate (3, 5) has three projections towards the corresponding laminar arch (A2, A3).

6. Prosthesis according to claim 5, characterized in that each plate includes a median projection (3A, 5A) designed for insertion into the spinal foramen of the vertebra and two laterally spaced apart lateral projections (3B, 3C; 5B, 5C) designed for insertion in contact with the corresponding outer surfaces (FB, FC; GB, GC) of the laminae forming the laminar arch (A2; A3).

7. Prosthesis according to claim 6, characterized in that said median projection is sufficiently thin so that it can be inserted into the spinal foramen of the vertebra without compressing the spinal cord.

8. Prosthesis according to one or more of the preceding Claims, characterized by connection means to connect said securing means (3, 5) to said elastic body (1).

9. Prosthesis according to claim 8, characterized in that said connection means include ligatures (7, 9), each of which passes through

first holes (3D, 3E; 5D, 5E) provided in said plates and corresponding second holes (1D, 1E) provided in said elastic body, said first holes and said second holes being in line with each other.

10. Prosthesis according to one or more of the preceding claims,
5 characterized in that each of said anchoring plates (3, 5) has a groove (3S, 5S) on the surface in contact with the elastic body (1), for the insertion of a corresponding tip (P2, P3) of divaricator forceps (P) in order to separate the vertebrae (L2, L3) between which the prosthesis is to be fitted.

11. Prosthesis according to claim 10, characterized in that said
10 grooves (3S, 5S) in the two plates are orientated parallel to each other.

12. Prosthesis according to one or more of the preceding claims, characterized in that it further includes an auxiliary ligament () for the spinous processes () of the two vertebrae (L2, L3) between which the prosthesis is introduced.

15 13. Prosthesis according to claim 12, characterized in that at least one of said plates includes engaging means () for engaging said auxiliary ligament.

14. Prosthesis according to claim 13, characterized in that each of
20 said plates includes engaging means () for engaging said auxiliary ligament.

15. Prosthesis according to claim 13 or 14, characterized in that said engaging means include at least one lateral hook () for at least one of said plates.

16. Prosthesis according to claim 13, 14 or 15, characterized in
25 that said engaging means include two lateral hooks () for each of said plates.

Fig. 2




Fig. 1




Fig. 3





Fig. 4









Fig. 6

Fig. 7









Fig.12

INTERNATIONAL SEARCH REPORT

Inventor's Application No
PCT/IT2004/000148

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B17/70

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	US 5 672 175 A (MARTIN JEAN RAYMOND) 30 September 1997 (1997-09-30) abstract; figures 1,15 column 16, lines 16-26	1-3,8,9 10
X	US 5 415 661 A (HOLMES DAVID C) 16 May 1995 (1995-05-16) abstract; figures 2,3 column 12, lines 48-50	1-3
X	US 5 725 582 A (BEVAN DAVID ROBIN ET AL) 10 March 1998 (1998-03-10) abstract; figure 5 column 5, line 56 - column 6, line 11	1,8
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *A* document member of the same patent family

Date of the actual completion of the international search

26 July 2004

Date of mailing of the international search report

04/08/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Macaire, S

INTERNATIONAL SEARCH REPORT

Int	ional Application No PCT/IT2004/000148
-----	---

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 281 362 A (SHOWA IKA KOHGYO CO LTD) 5 February 2003 (2003-02-05) abstract; figures 4-6 paragraph '0009! -----	1
A	US 5 562 737 A (GRAF HENRY) 8 October 1996 (1996-10-08) abstract; figure 11 column 5, lines 1-9 -----	1,2
A	US 6 074 390 A (ZUCHERMAN JAMES F ET AL) 13 June 2000 (2000-06-13) column 8, lines 15-22; figure 33 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/IT2004/000148

Patent document cited in search report.		Publication date	Patent family member(s)	Publication date
US 5672175	A	30-09-1997	NONE	
US 5415661	A	16-05-1995	AT 218046 T AU 6523694 A DE 69430697 D1 DE 69430697 T2 DK 690701 T3 EP 0690701 A1 ES 2177578 T3 WO 9421185 A1	15-06-2002 11-10-1994 04-07-2002 23-01-2003 23-09-2002 10-01-1996 16-12-2002 29-09-1994
US 5725582	A	10-03-1998	CA 2142836 A1 DE 69323636 D1 DE 69323636 T2 EP 0768843 A1 ES 2129522 T3 WO 9404088 A1 GB 2269753 A , B JP 8502668 T KR 275162 B1	03-03-1994 01-04-1999 01-07-1999 23-04-1997 16-06-1999 03-03-1994 23-02-1994 26-03-1996 15-12-2000
EP 1281362	A	05-02-2003	JP 2003038506 A EP 1281362 A2 US 2003109881 A1	12-02-2003 05-02-2003 12-06-2003
US 5562737	A	08-10-1996	FR 2712481 A1 AT 177305 T CA 2135838 A1 DE 69416937 D1 DE 69416937 T2 DK 654249 T3 EP 0654249 A1 ES 2130381 T3 FR 2712482 A1 JP 8191840 A	24-05-1995 15-03-1999 19-05-1995 15-04-1999 14-10-1999 27-09-1999 24-05-1995 01-07-1999 24-05-1995 30-07-1996
US 6074390	A	13-06-2000	US 5836948 A WO 0207623 A1 US 6149652 A US 2001016776 A1 US 6238397 B1 US 6280444 B1 US 2001007073 A1 US 2001012938 A1 US 2001039452 A1 AU 741210 B2 AU 5903498 A CA 2288252 A1 CN 1246041 A EP 0959792 A1 JP 2001507599 T WO 0191658 A1 WO 9829047 A1 US 6090112 A US 5876404 A US 6068630 A US 6048342 A US 6183471 B1	17-11-1998 31-01-2002 21-11-2000 23-08-2001 29-05-2001 28-08-2001 05-07-2001 09-08-2001 08-11-2001 22-11-2001 31-07-1998 09-07-1998 01-03-2000 01-12-1999 12-06-2001 06-12-2001 09-07-1998 18-07-2000 02-03-1999 30-05-2000 11-04-2000 06-02-2001

Form PCT/ISA/210 (patent family annex) (January 2004)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT2004/000148

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6074390	A	US 6156038 A	05-12-2000
		US 6379355 B1	30-04-2002
		US 6152926 A	28-11-2000
		US 6235030 B1	22-05-2001
		US 6190387 B1	20-02-2001
		US 6332882 B1	25-12-2001
		US 6419676 B1	16-07-2002
		US 6451020 B1	17-09-2002
		US 6332883 B1	25-12-2001
		US 2001020170 A1	06-09-2001
		US 2001031965 A1	18-10-2001
		US 2001016743 A1	23-08-2001
		US 2001021850 A1	13-09-2001
		US 2002183746 A1	05-12-2002
		US 2002029039 A1	07-03-2002
		US 5860977 A	19-01-1999

THIS PAGE BLANK (USPTO)